LED system light

Product-Nr.	155010-02
EAN:	
Model:	SYSTEMLED EVO - ECO Tageslichtweiss







Order number:	155010-02
Model:	SYSTEMLED EVO - ECO Tageslichtweiss
Type:	LED system light
Illuminant:	SMD LED
Total output incl. driver:	~13 W
Power consumption:	~11,5 W
Lamp luminous flux:	1990 lm
Lamp luminous efficiency:	173 lm/W
Light distribution:	direct
Light colour:	5700K 3-step MacAdam
Connected load:	120-277VAC, 50 - 60 Hz
Power supply:	integrated
Connection (connector):	Wieland GST18
Degree of protection:	IP40
Class of protection:	I
Glare control:	Microprisms
Beam angle (optics):	90°
Operating temperature:	-10 °C -> +50 °C (14 °F -> 122 °F)
Colour rendering (Ra):	>90 (typ. 95)
Lamps lifetime:	> 100.000h (L80/B10)
Housing material:	Aluminium, PMMA
Height [B] x Width [C]:	48 mm x 139 mm (~1,89“ x ~5,47“)
Length [A]:	472 mm (~18,58“)
Mounting:	T-slot rear (8 mm)
Risk group (DIN EN 62471):	free group
Markings:	CE, UKCA
Dimmable:	yes
Mounting accessories:	optional
Made in:	Germany
Feature:	externally dimmable/switchable

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com